

PATENT PENDING · DESIGN PATENT



- Evolution of the animal cage changing station
- Ergonomic design
- Eco-sustainability design
- Increased efficiency
- Acoustic comfort



LAMINAR FLOW

TECNIPLAST
*innovation through passion*SM



LAMINAR FLOW

CS5 Evo Changing Station

Evolution & Ergonomic Design

1&2



Eco-sustainability Design

3



1/Evolution of the Animal Cage Changing Station

The "CS5 EVO" is the ultimate Dual Access Animal Cage Changing Station with a superior ventilation system and airflow balancing technology providing personnel, environment and product protection during animal handling procedures.

2/Ergonomic Design

- Easy to move (only 160Kg/350lb) on 125 mm (5") casters with locking brakes.
- Angled viewing windows reduce glare and allow high visibility into the work area.
- The electronically controlled fluorescent lamps placed externally to the working area make for energy efficiency and provide optimal, uniform distribution of light over the work surface. A dimmer is available (option) to adjust the light intensity in case of manipulation of albino mice.
- The work surface height is electrically adjustable for ergonomic comfort and operator convenience.
- The ergonomic stainless steel integrated push/pull bar allows easy handling of the cabinet.
- When fully lowered to a height of 1921 mm (75.6") the cabinet can be wheeled from lab to lab.

3/Eco-sustainability Design

- Sustainable use of materials, using new technologies and manufacture process that conserve natural resources.
- Less steel and more Hi-Tech plastic molded parts.
- Sturdy construction and modern design.

4/Increased Efficiency

- The CS5 provides a large work area for one or two operators.
- The large work access opening makes it easy to introduce and remove cages from the work zone.
- The work surface is composed of two easily removable frames, built of sound-absorbent, anti-scratch, autoclavable material.
- Innovative dual configuration working surface design means that the working surface can be adjusted in height in order to create a recessed working area in case of manipulation of "popcorn" mice strain.
- Innovative airflow grille design on the peripheral work surface collect ambient air prevents clogging to maintain air barrier performance.

5/Acoustic Comfort

- Unique Tecniplast plenum design minimize noise and vibration.
- Two independent blowers are used, one for the supply filter and one for the exhaust filter.
- Continuous monitoring of cabinet airflow is displayed on a easy-to-read control panel. An acoustic and visual alarm signals when operational conditions are outside the set parameters.
- A microprocessor control system supervises operation of all cabinet functions and automatically control the constant airflow rate.

6/Containment and Protection

- The CS5 EVO with a new High Efficiency air plenum design and Laminar Airflow Technology (ISO5) protects the animals or products from external and cross-contamination, and protects the environment from allergens and particulate emissions.
- The CS5 EVO provides an excellent air curtain performance to protect investigators and animal care takers from exposure to allergens which can cause occupational hazards such as asthma and allergies.

7/High Cleanability

- High chemical resistance to Chlorine compounds.
- High-cleanability, perfectly rounded and smooth surface and edges.
- A protective net prolongs the lifespan and the efficiency of the HEPA filters positioned under the working area.
- A removable tank for refuse disposal and perimeter drain.

8/Wide Range of Accessories & Options


- "Easyfood" ABS dual chute feed hooper kit with plastic scoop.
- Folding shelf kit.
- Light Dimmer.
- Retractable Cable.
- "Sani-Jet" Spray Hand Sanitizer.
- Choice of colours.

9/Two Models Available

- CS5 Evo: Manual Adjustable Hydraulic Support Stand; Electronic manual adjustable airflow control; Retractable cable (optional).
- CS5 Evo Plus: Electric adjustable hydraulic support stand; Electronic automatic adjustable airflow control; Retractable cable (optional); Light dimmer (optional); Colour: Green (optional).


Increased Efficiency

4




Acoustic Comfort

5



Containment and Protection

6



Environment air Pre-filtered air HEPA filtered air

High Cleanability

7



TECHNICAL SHEET

Overall Dimension on electrical height adjustable floor stand (W x D x H):
1295 x 773 x 1921/2221 mm • 51 x 30.43 x 75.62/87.44 inch

Chamber Dimensions (W x D x H):
1000 x 600 x 640/680 mm • 39.37 x 23.62 x 25.2/26.8 inch

Access opening height:
340 mm • 13.4 inch

Weight:
160 kg • 350 lb

Electrical Supply:
230 V - 50/60 Hz • 100/115 V - 50/60 Hz

Control:
microprocessor driven with control panel

Classification of Air Cleanliness:
ISO 5 according to ISO 14644-1

Wide Range of Accessories & Options

8



Two Models Available

9



Related Products

To maximise operational efficiency and learn more about these products contact your local representative.



Sealsafe Plus: high containment, certified protection from allergens, high density and practicality of use. The IVC (r)evolution.



CSM: cage opening and closing operations, using the ultimate in robotic technology.



Logistic trolleys offer safety and ergonomic features that enable high load-density for moving cages and bottles, crates, pallets and covers.



Decontamination Lock. Full decontamination cycle, with 6 log reduction, in one hour all inclusive. The unit may be used with Vaporized Hydrogen Peroxide generators from different vendors, gaseous Chlorine Dioxide generators and for chemical fogging.

TECNIPLAST

HEADQUARTERS

ITALY | Tel. +39 0332 809711 • www.tecniplast.it • E-mail: tecnicom@tecniplast.it

SISTER COMPANIES

AUSTRALIA/NEW ZEALAND | Tel. + 61 2 8845 6500 • www.tecniplast.it • E-mail: info@tecniplast.com.au

FRANCE | Tel. 04 72 52 94 41 • www.tecniplast.fr • E-mail: info@tecniplast.fr

GERMANY | Tel. 08805 921320 • www.tecniplast.de • E-mail: info@tecniplast.de

UNITED KINGDOM | Tel. 0845 0504556 • www.tecniplast.it • E-mail: info@tecniplastuk.com

JAPAN | Tel. + 03 5770 5375 • www.tecniplast.it • E-mail: info@tecniplastjapan.co.jp

USA/CANADA | Toll Free: 877.669.2243 • www.tecniplastusa.com • E-mail: info@tecniplastusa.com

To find your local distributor, please visit www.tecniplast.it

